



Syndicate's Windshield TP is a non-transferable tamper-proof windshield UHF label that has been developed especially for automatic vehicle identification applications. Made using high-quality materials, the label does not expand or contract with changes in temperature. The label is tamper-proof, meaning any attempt made to remove the label results in breakage, thereby making it impossible to transfer the label to another vehicle. Made using a unique label construction, it is supplied in roll form as finished labels. It can be encoded and printed with typical UHF thermal transfer printers.

TYPICAL APPLICATIONS

- Automatic Toll Collection
- Parking Management
- Vehicle Access Control
- Electronic Vehicle Registration



PHYSICAL SPECIFICATION	
Face Stock	Printable white PET, resin ribbon is recommended
Label Sizes	90 x 27.0 x 0.2 mm 2.67 x 1.06 x 0.007 in
Adhesive	High performance permanent adhesive with excellent bonding to glass
Weight	2.5 gms
Delivery format	On reel
No. of Labels/ Reel	2000 pcs
Label Pitch	31.75 mm / 1.25 in
Core inner diameter	76 mm / 3 in




RF SPECIFICATION

Mode of Operation	Passive
Device type	Class 1 Gen 2 Passive UHF RFID transponder
Air interface protocol	EPC Global Class 1 Gen 2 ISO 18000-6C
Operational frequency	Global 860-960 MHz
IC type*	Alien Higgs 3
Memory configuration	EPC Size 96 Bits, User Memory 512 Bits, 96 bits TID with 64 bits Unique serial number
Data Retention	Upto 50 years
Read range (2W ERP)**	ETSI : On Glass upto 11 m / 36 ft FCC : On Glass upto 11 m / 36 ft
Applicable surface materials	Glass

ENVIRONMENTAL RESISTANCE

Operating Temperature	-30°C to +85°C / -22°F to +185°F
Withstands Exposure To	Tested at 85°C / 185°F for one month, no change in electrical behavior observed
Peak Temperature	85°C / 185°F
Adhesive Service Temperature	+70°C / 158°F
Recommended Application Temperature	+10°C to +38°C / 50°F to +100.4°F
Water Resistance	IP68, tested for 5 hours in 1m deep water
Ideal Storage Condition	+23°C, 50% RH / +73°F, 50% RH
Expected Lifetime	Years in normal operating conditions

PRODUCT INSTALLATION



- Ideal application conditions are +23°C (+78°F) / 50% RH. Ensure the application surface is even and is clean and dry, to obtain maximum bond strength. If required, use approved cleaning solvents to clean surface. Bond strength can be improved by applying firm pressure. Avoid touching the exposed label adhesive while mounting it.
- Label's antenna parts should not come in contact with metal to ensure better performance. Also note that metallized UV-protection films effect RFID performance.
- Do not bend the label beyond the prescribed limit. Avoid touching the IC location as well as applying excessive pressure, as it is a sensitive electrical component and might get damaged.

PERSONALIZATION OPTIONS

Pre-encoding

- Customer specific encoding of EPC

Customized Printing

- Customer specific layout including logo & text, numbers, barcodes etc.

ORDER INFORMATION


Part Number

- RF.LI.WS.TP.H3

Roll Sizes

- 2000 Labels per Roll / 4 Rolls per Carton

READ RANGE GRAPH



* Other IC's available on request

** The indicated read range values are measured in our laboratory testing environment, where antennas with optimum directivity are used with maximum allowed operating power. Different surface materials and environments may exhibit different results.



Version : 140119.01