


DATASHEET

MINITRACK

Best in class performance for pharmaceutical and product authentication applications.



MiniTrack tags and inlays are small sized, high end products for demanding item level applications.

Benefits:

- ▶ Suitable for small item level packages, wristbands and other demanding applications.
- ldeal match for applications where embedding the inlay is a must.
- ▶ Small sized product for easy labelling and stickers.
- ▶ ISO 9001:2008 Quality Management System and ISO 14001:2004 Environment Management System support.

Overviev

Operating Frequency

13.56 MHz

Integrated Circuit (IC)

NXP ICode SLIX

Antenna Size

14 x 31 mm (0.55 x 1.22 in)

Die-cut Size

18 x 36 mm (0.71 x 1.42 in)

International Standards

ISO 15693

ISO 18000-3 Mode 1

Quality Assurance

100% performance tested

Application Areas

- Pharma and Healthcare
- Product Authentication
- Brand Protection
- Ticketing
- Library and Media Management



MINITRACK

Technical Features	
IC	NXP ICode SLIX
Memory	1k bit
Frequency	13.56 MHz
Antenna Size	14 x 31 mm / 0.55 x 1.22"
Die-cut Size	18 x 36 mm / 0.71 x 1.42"
Web Width	26 mm / 1.02"
Operating Temperature	-40°C to 85°C / -40°F to 185°F
Bending Diameter (D)	> 50 mm, tension max. 10 N
Delivery Formats	Dry inlay, wet inlay, tag
Adhesive	Permanent pressure sensitive adhesive
Adhesive Usage Temperature	min10°C to 90°C / min. 14°F to 194°F
Qty/Reel	2,500 per reel
Core Size	76 mm / 3"
Shelf Life: minimum of 2 years from the date of manufacture in	20°C / 68°F, 50% RH

SMARTRAC TECHNOLOGY GROUP uses three different qualification methods to evaluate the quality and reliability of RFID inlay and tag products. Products are tested according to IEC 60068-2-67 (temperature and humidity), JESD22-A104-B (temperature cycling) and an in-house developed bending test.



For further information, please contact our sales representatives:

Sales Europe SMARTRAC TECHNOLOGY GROUP

Hanauer Landstrasse 291a 60314 Frankfurt am Main Germany Tel. +49 69 904 3579 1011

Fax +49 69 904 3579 1015 sales.emea@smartrac-group.com

Sales Americas

SMARTRAC TECHNOLOGY Fletcher Inc. 267 Cane Creek Road Fletcher, NC 28732 United States of America Tel. +1 866 901 7343 Fax +1 828 651 6063 sales.americas@smartrac-group.com

Sales APAC

SMARTRAC TECHNOLOGY PTE. Ltd. SINGAPORE 6 Greenleaf Walk Amsterdam Building 2-8 Singapore 279226 Tel. +60 4 489 36-0 Fax +60 4 489 36-50 sales.apac@smartrac-group.com

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.