

XT5-40 Series

4 inch Thermal Transfer Industrial Label Printer



Retail



Warehouse



Logistics



Manufacturing


Premium Performance



RFID



GOD DESIGN



Standard Auto cutter Peeler Rewinder + Peeler



Accurate RFID Performance

- The XT5-40NR supports UHF RFID print and encode capability
- Extremely close-spaced RFID inlay encoding supported (minimum pitch of 0.6 inch / 16 mm)
- RFID auto-calibration simply reads the RFID tag location

Durability and User Convenience

- Aluminum body and special adhesiveless metal case
- Space-saving design with double folding door
- 3.5 inch full colour or 4.3 inch full colour touch LCD display
- Printing speed up to 14 ips (356 mm/sec)
- 203, 300 or 600 dpi resolution
- The industry's fastest Ethernet (1Gbit/sec) embedded
- Toolless maintenance of roller and print head
- General-purpose I/O (GPIO) interface for factory automation

Enhanced Softwares

- SoftAP: Simple Wi-Fi set up to a mobile device
- Twin function™: Copy printer settings and data via USB storage
- XPM™: BIXOLON's web-based profile manager (Optional)



BIXOLON
a Better Solution for your Business™

XT5-40 Series

4 inch Thermal Transfer Industrial Label Printer

Specifications

Printer Specifications

Print Method

Thermal Transfer, Direct Thermal

Print Speed

XT5-40: Up to 14 ips (356 mm/sec)

XT5-43: Up to 10 ips (254 mm/sec)

XT5-46: Up to 5 ips (127 mm/sec)

Print Resolution

XT5-40: 203 dpi

XT5-43: 300dpi

XT5-46: 600dpi

Print Width

XT5-40: 104mm

XT5-43: 105.7mm

XT5-46: 105.6mm

Print Length

XT5-40: Up to 4,000 mm

XT5-43: Up to 2,500 mm

XT5-46: Up to 1,000 mm

Sensor

Transmissive(Adjustable),
Reflective (Adjustable), Ribbon-End,
Head open

Media Characteristics

Media Type

Gap, Black Mark, Notch, Continuous,
Fan-Fold

Media Width

25 ~ 114 mm

Media Roll Diameter

Up to 203 mm

Media Thickness

0.06 ~ 0.30 mm

Supply Method

Easy Paper Loading

Inner Core

38.1 ~ 76.2mm, 25.4mm (option)

Ribbon Characteristics

Ribbon Type

Wax, Wax/Resin, Resin, Outside, inside

Ribbon Width

50 ~ 110 mm

Ribbon Length

Up to 450 m

Core Inner Diameter

25.4 mm

Physical Characteristics

Dimensions (W x D x H)

STD: 269 x 490 x 324 mm
(10.59 x 19.29 x 12.76 inch)

Rewinder: 269 x 490 x 407 mm
(10.59 x 19.29 x 16.02 inch)

Weight

STD: 13.98Kg (30.82 lbs.)

Rewinder: 17.98Kg (39.64 lbs.)

Electrical

EnergyStar Certified,
Internal Power Adaptor 100-120V/200-240V AC,
50/60Hz

Display

XT5-40 : 3.5 inch full color LCD

XT5-40N : 4.3 inch full color touch LCD

Performance Characteristics

Memory

512 MB SDRAM, 512 MB Flash

Interface

Standard:
USB + Serial + Ethernet¹ + 2 USB Host ports

Optional:

- ① USB + Serial + Parallel or GPIO + Ethernet + 2 USB Host ports
- ② USB + WLAN¹ + Ethernet + 2 USB Host ports
- ③ USB + WLAN¹ + Parallel or GPIO + Ethernet + 2 USB Host ports
- ④ USB + Bluetooth + Ethernet + 2 USB Host ports + WLAN²
- ⑤ USB + Bluetooth + Parallel or GPIO + Ethernet + 2 USB Host ports + WLAN²

Ethernet: 10/100/1000Mbps (1Gbps)

WLAN¹: 802.11a/b/g/n (Infrastructure, Ad-hoc,
Wi-Fi Direct, SoftAP)
- WEP40/104, WPA1/2 (PSK, EAP)

WLAN²: 802.11a/b/g/n Dongle type - requires a USB
Host port (Optional)

Bluetooth: V4.2 (MFi certified)

GPIO: DB15(Female), 5/24V, 4 GPI, 8 GPO

Real Time Clock

Supported (Standard)

Environment Characteristics

Temperature

Operating: 5 ~ 40°C (41 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

Software

Emulation

SLCST[™], BPL-Z[™], BPL-E[™], BPL-D[™]

Driver / Utility

Windows Driver (Europlus / Seagull),

Linux / Mac CUPS Driver,

Virtual COM USB / Ethernet Driver, Utility Program,

OPOS / JPOS Driver, Bartender Ultralite for BIXOLON,

Label Artist-III[™], SAP[®] Device Driver,

Network Auto Installer

SDK / Plugin

Android / iOS / Windows SDK, Linux SDK,

Chrome SDK, Xamarin SDK, Web Print SDK

Application

Label Artist[™] Mobile (Android, iOS),

mPrint App (Android, iOS)

MDM (Optional)

BIXOLON Profile Manager

- XPM[™], XCM[™] (Windows, Android)

XI (Optional)

Supported

Fonts / Graphics / Symbologies

Fonts

Bitmap Fonts (10 SLCST[™], 16 BPL-Z[™], 5 BPL-E[™],
9 BPL-D[™]), Scalable Fonts (1 SLCST[™], 1 BPL-Z[™],
1 BPL-D[™]), 23 Code page,
Unicode supported (UTF-8, UTF-16LE, UTF-16BE)

Graphics

Supporting user-defined fonts, graphics,
formats and logos

Barcode Symbologies

1D: Codabar, Code 11, Code 39, Code 93, Code 128,
EAN-13, EAN-8, Industrial 2-of-5,
Interleaved 2-of-5, Logmars, MSI, Plessey,
Postnet, GS1 DataBar (RSS-14), Standard 2-of-5,
UPC/EAN extensions, UPC-A, UPC-E, IMB

2D: Aztec, Codablock, Code 49, Data Matrix,
MaxiCode, MicroPDF417, PDF417, QR code,
TLC 39

Accessories

Optional

Peeler, Auto Cutter, Rewinder,

1" I.D. Core media supply hanger, Serial cable,

Parallel cable, USB cable

Supplies

Compatible with B-ribbon[™]

RFID

Frequency

UHF, 865 ~ 868MHz (EU), 902 ~ 928MHz (KR, USA)

Transmit Power

1W

Modulation

ASK

Protocol

ISO 18000-6C(EPC Class1 Gen2)

Auto Cutter

Optional

Tag Pitch

Min 16mm