



## Flexible and Extensible Fixed Readers for RAIN RFID Solutions

The Speedway R420 and R220 readers deliver the performance, quality, and reliability necessary for maximum visibility of tagged inventory and assets. Able to maintain high read rates regardless of RF noise or interference as the readers adapt automatically for optimal functionality, Speedway readers are a powerful piece of item visibility platform solutions. Speedway readers are supported by a suite of software, hardware and antennas that deliver application and deployment flexibility, making installation and expansion easier than ever.

### Speedway Reader Features and Benefits

- Available in 2 or 4 antenna port configurations, expandable to 32 antennas with Speedway Antenna Hub to deliver lower total cost of ownership and greater application flexibility
- Exclusive, patented Autopilot capability simplifies deployment and delivers more than 1,100 tag reads per second by automatically optimizing settings for best, most reliable, and efficient performance:
  - Autoset: Continuously senses environmental RF noise and interference levels, automatically selecting appropriate reader configuration settings
  - Low duty cycle: Reduces RF interference, power consumption, and energy cost by only transmitting when tags are in field
  - Dynamic antenna switching: senses where tags are in the field and automatically focuses more time on the antennas with the largest tag populations in view
- The industry's highest RF sensitivity (-84dBm) provides greater accuracy and longer read ranges
- Simple deployment via Power over Ethernet (PoE), with enterprise-class management and monitoring
- Field-proven, enterprise-class durability with high mean-time between failure



### Software Tools

Our software is built to simplify deployment of Item Intelligence solutions. Impinj **ItemSense** software aggregates and transforms torrents of raw RAIN RFID data from multiple readers into Item Intelligence information that integrates with third-party applications. ItemSense is scalable, flexible, and extensible, adapting to businesses as they grow to connect more items, more readers, and more locations. It facilitates a broad range of solutions for retailers, manufacturers, and healthcare providers.











#### Other software includes:

- **Speedway Connect** is an on-reader application that enables you to easily set configurations for a single reader and quickly access RAIN RFID data through a simple web-based interface.
- Advanced users can quickly build on-reader applications with the **Speedway Embedded Took Kit (ETK)** or develop hosted applications that access the LLRP toolkit (LTK) through the **Octane Software Development Kit (SDK)**.
- For high-throughput encoding operations, **ItemEncode** software boosts the speed and data quality of RAIN RFID encoding machines while lowering labor and operating costs.

## Hardware Accessories

Impinj's **Speedway Antenna Hub** provides a low-cost opportunity to create a large, contiguous RAIN RFID read zone with many antennas connected to a single reader. The Speedway Antenna Hub supports up to 32 antennas connected to a single Speedway Revolution R420 reader for a robust solution to today's popular item monitoring and other antenna-intensive RFID applications, which deliver enhanced business intelligence and customer experience. The Speedway Antenna Hub makes RFID monitoring applications, including smart shelves, interactive marketing displays, and document or item tracking, cost-effective and easy to deploy. Our **GPIO box** provides convenient access to Speedway readers' General Purpose Input/Output ports giving you the ability to add sensors and triggers to your application.

### Antennas Optimized for Item-Level Tracking Solutions

Product	Application	Dimensions	Range
<p>Brickyard Antenna</p> 	<p>The Brickyard reader antenna works well for tagged items on a variety of package types, making it an ideal choice for point-of-sale applications.</p>	29.5 cm x 6 cm	<p>Short (30-45 cm)</p> 
<p>Guardwall Antenna</p> 	<p>The Guardwall reader antenna provides a tightly controlled read zone and intense RF field, critical to penetrating deep into packed cases travelling on conveyors or packing lines.</p>	70 x 40 x 10 cm	<p>Long (3 m) alone, shorter (variable) when used in a pair</p> 
<p>MatchBox Antenna</p> 	<p>With its diminutive size, the MatchBox reader antenna is ideally suited for embedded applications that require unobtrusive RAIN RFID capability with short-range, well-defined read zones.</p>	7.3 x 3.3 x 1.1 cm	<p>Very short (3.5 cm)</p> 
<p>Mini-Guardrail Antenna</p> 	<p>The Mini-Guardrail reader antenna, specifically designed for demanding item-level performance, operates very effectively at 7.5 cm or less, with high reliability and a constrained read zone.</p>	13 x 7 x 2cm	<p>Very short (7 cm)</p> 
<p>Threshold Antenna</p> 	<p>The Threshold antenna provides a consistent and continuous read zone when linearly distributed head-to-tail, with a planar form factor that fits readily into doorways for traffic monitoring.</p>	46 x 9 x 2 cm	<p>Long (4 x 3 m)</p> 

Product Details	Speedway R420	Speedway R220																
Air Interface Protocol	GS1/EPCglobal UHF Gen2 (ISO 18000-6C) or RAIN RFID																	
Antenna Ports	4 expandable to 32 antennas with Speedway Antenna Hub optimized for Impinj reader antennas (RP TNC connector)	2 monostatic antenna ports optimized for Impinj reader antennas (RP TNC connector)																
Performance	Optimized for high volume, high concentration scenarios; supports high throughput modes including Max Throughput FM0, Hybrid (m=2), and Max Miller (m=4)	Covers a smaller, more specific area to save on deployment costs																
Supported Regions or Geographies	Go to <a href="http://www.impinj.com/supported_regions">www.impinj.com/supported_regions</a> for regions and geographies by model																	
Transmit Power	<ul style="list-style-type: none"> <li>+10.0 to +31.5 dBm (PoE) (EU1 limited to +30 dBm)</li> <li>+10.0 to +32.5 dBm (Listed/Certified power supply) (EU1 limited to +31.5 dBm, JP2 limited to 30 dBm)</li> </ul>																	
Max Receive Sensitivity	-84 dBm																	
Min Return Loss	10 dB																	
Application Interfaces	<ul style="list-style-type: none"> <li>Low Level Reader Protocol (LLRP): C, C++, Java, and C# libraries</li> <li>OctaneSDK: Java or C#</li> <li>On-reader Applications via Octane ETK: C, C++</li> </ul>																	
Network Connectivity	<ul style="list-style-type: none"> <li>10/100BASE-T auto-negotiate (full/half) with auto-sensing MDI/MDX for auto-crossover (RJ-45)</li> <li>802.1x with PEAP/TLS and MD5 support</li> <li>WPA for Wifi and Ethernet</li> <li>Speedway Connect (not included in Speedway purchase): HID (keyboard) emulation,</li> <li>TCP Socket, Serial/RS-232, HTTP POST</li> </ul>																	
IP Address Configuration	DHCP, Static, or Link Local Addressing (LLA) with Multicast DNS (mDNS)																	
Time Synchronization	Network Time Protocol (NTP)																	
Management Interfaces	<ul style="list-style-type: none"> <li>Impinj Web Management UI</li> <li>Impinj RShell Management Console using serial management console port, telnet, or SSH</li> <li>SNMP</li> </ul>	<ul style="list-style-type: none"> <li>FTP</li> <li>EPCglobal Reader Management v1.0.1</li> <li>Syslog</li> </ul>																
Reliable Firmware Upgrade	<ul style="list-style-type: none"> <li>Dual image partitions enable smooth transition to new firmware while the reader is still operating</li> <li>Scalable upgrade mechanism enables simultaneous scheduled upgrades of multiple readers</li> </ul>	<ul style="list-style-type: none"> <li>USB Flash Drive</li> <li>Impinj Web Management UI</li> <li>SSH File Transfer Protocol (SFTP) support</li> </ul>																
Management Console	RS-232 using a standard Cisco-style management cable (DB-9 to RJ-45)																	
USB	<ul style="list-style-type: none"> <li>USB Device (Type B) and Host (Type A) ports</li> <li>USB Virtual COM Serial Port and USB drive support for embedded applications</li> </ul>																	
GPIO	4 inputs, optically isolated 3-30V; 4 outputs, optically isolated, 0-30V, non-isolated 5V, 100mA supply (DB-15)																	
Power Sources	<ul style="list-style-type: none"> <li>Power over Ethernet (PoE) IEEE 802.3af</li> <li>Listed/Certified power supply, marked LPS or Class 2, with 24Vdc output, rated minimum 2.5A</li> </ul>																	
Power Consumption	<table border="1"> <thead> <tr> <th></th> <th>Idle</th> <th>Typical</th> <th>LDC</th> </tr> </thead> <tbody> <tr> <td>PoE at +30 dBm</td> <td>3W</td> <td>11.5W</td> <td>6W</td> </tr> <tr> <td>Power Supply at +30 dBm</td> <td>3W</td> <td>13.5W</td> <td>6W</td> </tr> <tr> <td>Power Supply at +32.5 dBm*</td> <td>3W</td> <td>15W</td> <td>6W</td> </tr> </tbody> </table>		Idle	Typical	LDC	PoE at +30 dBm	3W	11.5W	6W	Power Supply at +30 dBm	3W	13.5W	6W	Power Supply at +32.5 dBm*	3W	15W	6W	*Maximum is 31.5 dBm for EU1 readers and 30dBm JP2 readers
	Idle	Typical	LDC															
PoE at +30 dBm	3W	11.5W	6W															
Power Supply at +30 dBm	3W	13.5W	6W															
Power Supply at +32.5 dBm*	3W	15W	6W															
Environmental Sealing	IEC IP52																	
Shock and Vibration	Mil-Std-810G Certified																	
Electrical Safety	UL Listed (US and Canada), EN 60950-1:2006 / A11:2009 / A1:2010 / A12:2011																	
Operating Temperature	-20 °C to +50 °C																	
Humidity	5% to 95%, non-condensing																	
Dimensions & Weight	7.5 in H x 6.9 in W x 1.2 in D (19 x 17.5 x 3 cm); 1.5 lbs (24.5 oz)																	
RoHS	Compliant to European Union directive 2011/65/EU																	
Warranty and Maintenance Options	<ul style="list-style-type: none"> <li>1 year limited warranty with purchase, option to extend</li> <li>3 year Enhanced Maintenance upgrade available</li> </ul>																	



Copyright © 2011-2015 Impinj, Monza and Speedway are registered trademarks of Impinj, Inc. These products may be covered by one or more U.S. patents. See [www.impinj.com/trademarks](http://www.impinj.com/trademarks) and [www.impinj.com/patents](http://www.impinj.com/patents) for details. Other brands and names may be claimed as the property of others.

