

## DL-210/310

The fast  
entry-level variant



### HIGHLIGHTS AT A GLANCE:

- Easy and Quick media loading
- Variety of interfaces
- Supports ZPL and EPL emulation
- Optional Cutter
- 300 m ribbon and 5 inch (127 mm) media capacity



# DL-210/310

Tally Dascom's DL-210 thermal transfer printer offers reliability, precision and performance in desktop size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media and ribbon loading. The clear panel enable simple and effective operation making it very simple to use.

The DL-210 is easily integrated into existing systems as there are several interfaces also available. In addition to this, the DL-210 is also available with an optional cutter to meet industry requirements.

## TECHNICAL DATA

<b>Print Speed</b>	DL-210: 6 ips (152 mm/sec.) DL-310: 4 ips (102 mm/Sek.)
<b>Print Width</b>	DL-210: 108 mm DL-310: 102 mm
<b>Print Method</b>	Direct Thermal or Thermal Transfer
<b>Resolution</b>	DL-210: 203 dpi DL-310: 300 dpi
<b>Fonts</b>	Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM
<b>Printhead Lifetime</b>	30 km or 6 months
<b>Memory</b>	DL-210: 8 MB Flash, 8 MB SDRAM DL-310: 8 MB Flash, 16 MB SDRAM
<b>Interfaces Standard</b>	USB (2.0 Full Speed)
<b>Interfaces Optional</b>	Serial (RS-232C), Parallel (IEEE 1284), Ethernet (10/100)
<b>Emulations</b>	ZPL II, EPL
<b>Consumables</b>	Ribbon, Direct Thermal/ Thermal Transfer paper and labels
<b>Ribbon</b>	Width: 33 - 110 mm; Length: 300 m Core diameter: 1" (25,47 mm); Outside diameter: 68 mm
<b>Media</b>	Width: 25 - 118 mm; Thickness: 0,06 - 0,18 mm Core diameter: 1" or 1,5" (25,4 mm or 37 mm); Outside diameter: 5" (127 mm)
<b>Sensors</b>	Black Mark, Label Gap, Farbband
<b>Barcode</b>	1D: Code 11, Interleaved 2-of-5, Code 39, Code 49, Code 93, Code 128, Planet Code, EAN 8, EAN 13, UPC-E, UPC-A, Industrial 2 of 5, Standard 2 of 5, Codabar, MSI, Plessey 2D: PDF 417, MaxiCode, QR Code, Data Matrix
<b>Physical Weight</b>	3 kg
<b>Physical Size</b>	230 x 290 x 176 mm (W x D x H)
<b>Power Voltage</b>	100 - 240 V AC - 50/60 Hz
<b>Temperature</b>	+5° to +40° C
<b>Humidity</b>	10% to 98% (non condensing)
<b>Print Volume</b>	up to 300 m/day
<b>Printer Driver</b>	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022
<b>Options</b>	Models with cutter or peeler; Serial, Parallel, Ethernet interface

### Configurations:

- **DL-210/310** Standard product (USB only)
- **DL-210/310 Ser** Model with USB & ser. interface
- **DL-210/310 Par** Model with USB & par. interface
- **DL-210/310 Eth** Model with USB & Ethernet interface

**DASCOM GB Ltd**  
Hart House, Priestley Road  
Basingstoke | Hampshire RG24 9PU | ENGLAND  
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400  
info.gb@dascom-com | www.dascom.co.uk

**DASCOM Europe GmbH**  
Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

**DASCOM (Holdings) LTD.**  
R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047