













C72

UHF RFID Reader

-  Android
-  4G
-  WiFi
-  Bluetooth
-  UHF
-  1D Barcode
-  2D Barcode
-  NFC
-  Camera
-  GPS

Chainway C72 is an Android rugged mobile computer. It features powerful processor, 8000mAh battery and superb UHF RFID capability. It can be equipped with R2000 linearly or circularly polarized antenna. That it can read tags in bulk from long distance enables it to be deployed in asset management, retail, warehousing, fleet management and etc.



Specification

Performance

CPU	Cortex-A53 2.5 GHz Octa-core
RAM+ROM	3 GB + 32 GB 4 GB + 64 GB (optional)
Expansion	Supports up to 128 GB Micro SD card
Operating System	Android 8.1; Soti MobiControl, SafeUEM supported

Communication

WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna
WWAN (China)	2G: 900/1800 MHz
	3G: WCDMA: B1,B8
	CDMA2000 EVDO: BC0
	TD-SCDMA: B34,B39
WWAN (Overseas)	4G: B1,B3,B5,B8,B34,B38,B39,B40,B41
	2G: 850/900/1800/1900 MHz
	3G: B1,B2,B4,B5,B8
WWAN (Others)	4G: B1,B2,B3,B4,B5,B7,B8,B12,B17,B20,B25,B40,B66
	Depending on the country's ISP
Bluetooth	Bluetooth v2.1+EDR,3.0+HS,v4.1+HS
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna

Physical Characteristics

Dimensions	164.2 x 80.0 x 24.3 mm / 6.46 x 3.15 x 0.96 in.
Weight	654 g / 23.07 oz.
Display	5.2" IPS FHD 1920 x 1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Li-ion, rechargeable, 8000 mAh
	Standby: over 500 hours
	Continuous use: over 12 hours (depending on user environment) Charging time: 3-4 hours (with standard adaptor and USB cable)
Expansion Slot	1 slot for SIM card, 1 slot for SIM or TF card
Interfaces	USB 2.0 Type-C, OTG, TypeC headphones supported
Audio	Speaker, 2 microphones
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
Sensors	Gravity sensor, light sensor, proximity sensor

User Environment

Operating Temp.	-4 °F to 122 °F / -20 °C to 50 °C
Storage Temp.	-40 °F to 158 °F / -40 °C to 70 °C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.9 ft. drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	Host IP65 per IEC sealing specifications
ESD	±15 KV air discharge, ±6 KV conductive discharge

Developing Environment

SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

Data Collection

Camera

Camera	13 MP Autofocus with flash
---------------	----------------------------

RFID (Optional)

UHF

Engine	CM2000-1 module based on Impinj Indy R2000
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Linear polarization(1.8dBi); circular polarization (4dBi)
Power	1 W (30 dBm, +5 dBm to +30 dBm adjustable)
	2 W Optional (33 dBm, for Latin America, etc.)
R/W range	>25 m (circular polarization, indoors); >15 m (circular polarization, open outdoors, Impinj MR6 tag); >21 m (linear polarization, indoors); >7 m (linear polarization, open outdoors)
	Fastest Read Rate 900+ tags/sec (circular polarization)

* Ranges and rates depend on tags and environment

Barcode Scanning (Optional)

1D Linear Scanner	Zebra: SE965; Honeywell: N4313
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scanner	Zebra: SE4710 / SE4750 / SE4750MR; Honeywell: N6603
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

NFC (optional)

Frequency	13.56 MHz
------------------	-----------

Accessories

Standard	AC Adaptor, USB Cable, etc.
Optional	Cradle, Holster , etc.

* For detailed specification, please check Accessory Guide.

Notice: Product specifications are subject to change without prior notice. / Model: C72UHF / Update Date: 2020-11-16

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: <http://www.chainway.net>