

sewoo

Cost-effective and Weight light Receipt/Label Printer

LK-P41



- Competitive low price
- Excellent Compatibility
- Ultra Compact and Lightweight
- Durable and resistant to water and dust
- S-MDM (SSM & SCM)
- Accessories : Shoulder Strap, Car Charger, Leather case



WiFi



Bluetooth



Barcode



Portable




Durable



Drop Resistant



Easy Loading



Compact Design



Easy Maintenance



Improved Battery Life



S-MDM Support



APPLICATION



SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal

Print Speed
Up to 3,1ips (80mm/sec)

Print Width
Up to 4.1" (104mm)

Resolution
203 dpi (8dots/mm)

Memory
4MB SRAM, 8MB Flash

Battery Voltage / Capacity
7.4V / 2600mAh.
(Optional) 5,200Ah
Rechargeable Li-ion battery

Sensor
Paper end, Gap,
Black mark, Cover open

Reliability
TPH life : 50km

CERTIFICATIONS

KC, FCC, UL/cUL, Mfi

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
5.87" × 6.37" × 2.75"
(149 × 162 × 70mm)

Weight
1.2lb(572g, With 2,200mAh battery)

INTERFACES

Standar
USB, Serial(RS-232C)

Optional
Bluetooth 2.1,
Wi-Fi(802.11a/b/g/n)

ACCESSORIES

Standard
USB Cable, Serial Cable,
Battery Pack, Thermal Roll Paper,
Battery Charger (8.4V)

Optional
Shoulder Strap, Cigar Jack,
Battery Cradle, Leather Case

OPERATING CHARACTERISTICS

Operating Temperature
14 ~ 122°F(-10 ~ 50°C)

Operating Humidity
35 ~ 80%

Storage Temperature
-4 ~ 140°F(-20 ~ 60°C)

Storage Humidity
10 ~ 90%

Dust-and Water-resistance Rating
IP54(With case)

Drop Rating
3.9ft.(1.2m, Set only) to concrete
5.9ft.(1.8m, With case) to concrete

BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13, EAN-13
(+2+5), Codabar, Code11, Code39,
Code93, Code128, ITF, LUPC-A(+2+5),
UPC-E, UPC-E(+2+5), Planet, UPC-A etc

2D
QR, PDF417, MicroPDF417, Maxicode,
Datamatrix, Aztec, RSS14, TLC39

SOFTWARE

Emulations
ESC/POS, CPCL, ZPL Command
compatible

Drivers
Windows Driver(XP ~, Server2003 ~),
Window CE & Mobile Driver & SDK
(CE 4.2~, Mobile 5.0~), Linux Driver,
Mac Driver, OPOS Driver,
JavaPOS Driver, iOS SDK,
Android(6.0 ~) SDK

MEDIA CHARACTERISTICS

Media Type
Thermal paper/label

Media Width
1.9"~ 4.4"(50~112mm)

Media Core Diameter
0.4" (12.5mm ± 0.5mm)

Media Roll Diameter
Ø 2.2"(56mm)

Thickness
0.06 ~ 0.16mm

FONTS / GRAPHICS

Character Size
Font A(12×24), Font B(9×17),
Asian Font(KOR,JPN,CHN-GB2312,
CHNBig5), Font0/1/2/4/5/6/7,
Resident TTF, Downloadable TTF,
FontA~H, FontGS, Residnt TTF(Font0),
Font 1~8

Characters per Line (CPL)
Font A(12x24): 69cpl,
Font B(9x17): 92cpl,

Character Set
95 Alphanumeric,
14 International,
128 * 18 page

sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea
T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

USA, Inc.

Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_sales@miniprinter.com

México Office

Cuauhtémoc, D.F. Mexico. CP 06500
T. +52-1-55-3232-9543 M. +52-1-55-143893
E. LA_sales@miniprinter.com

China Office

Shang hai shi, Song jiang qu
T. +86-177-1729-9100
E. sales@miniprinter.com

