

Content

1. Configuration	2
Note: the asterisk(*) to the factory default	2
2. output mode	2
3. Data Transfer Mode	2
4. Communication Mode	3
5. USB interface type	4
6. USB-HID Data type	5
7. Storage Mode	6
8. Battery Function	6
9. Motor Mode Set	7
10. Sound Volume Set	7
LOW	7
11. Sound Type	8
12. Sound frequency setting	8
Sound frequency 2700HZ	8
13. Sleep Time Set	8
14. GS (group separator) characters conversion	9
15. Letter case conversion	10
16. Language Set	11
17. ①2.4G Wireless Setting Private	13
21. Bluetooth Setting Private	14
18. Show or Hide the Keyboard in IOS	16
19. Bluetooth HID Transfer Rate	16
20. Bluetooth SPP Mode	17
21. Bluetooth BLE Mode	17
22. Bluetooth Name Setting	17
23. Get Bluetooth Name	18
24. Get Bluetooth Address	19
25. Software Update	19
26. Data editor	20
27. Hide front character shortcut settings	23
28. Hide the following characters shortcut settings	25

1. Configuration

Note: the asterisk(*) to the factory default



^&001&^

Firmware version



^&002&^

Factory default

2. output mode



^&05A&^

USB priority output(*)

Note: When a USB is inserted, only transfer via USB



^&05B&^

At the same time the output

Note: USB and 2.4g or bluetooth output at the same time

3. Data Transfer Mode



^&005&^

Normal run mode

Note: In normal mode, the scanned data will be uploaded immediately. If the transmission fails, an alarm will be issued, and the data will not be saved.



^&006&^

Storage run mode

Note: In inventory mode, the scanned barcode will be automatically saved. If you need to view statistical data or upload data, you can scan the corresponding set barcode to view it.



^&007&^

Automatic storage mode

Note: In automatic storage mode, the data will be automatically saved when the distance is exceeded. When you need to upload the automatically saved data, scan the setting code "Upload all data" to upload the automatically saved data


4. Communication Mode



^&010&^

Receiver Mode

Note: To re-pair another receiver, please see the Pairing 2.4G Receiver Function section for details



^&011&^

Bluetooth HID Mode


Note:Bluetooth HID mode is to switch to HID mode, and the previously paired Bluetooth will be automatically connected. When there is a problem with the bluetooth communication, the alarm prompts that the bluetooth entry is unsuccessful.



^&012&^

Bluetooth BLE Mode

Note:In Bluetooth BLE transparent transmission mode, Bluetooth devices (ie, Bluetooth devices such as mobile phones/IPADs) need to download or develop low-power Bluetooth BLE transparent transmission software before they can be used. When there is a problem with the Bluetooth communication, the alarm prompts that the Bluetooth entry is unsuccessful.



^&013&^

Bluetooth SPP Mode

Note:In the Bluetooth SPP transparent transmission mode, Bluetooth devices (ie, Bluetooth devices such as mobile phones/IPADs) need to download or develop classic Bluetooth SPP transparent transmission software before they can be used. When there is a problem with the Bluetooth communication, the alarm prompts that the Bluetooth entry is unsuccessful.

5. USB interface type



^&015&^

USB-HID(*)



^&016&^

USB-COM

6. USB-HID Data type



^&051&^

Keyboard function key



^&052&^

Send Chinese Characters




^&053&^

Send ASCII

7. Storage Mode



^&030&
Clear all data



^&031&
Statistical Information



^&032&
Uploading all data

8. Battery Function



^&037&
Battery Indicator

9. Motor Mode Set



^&038&^

OFF



^&039&^

ON(*)

10. Sound Volume Set



^&03A&^

OFF



^&03B&^

HIGH(*)



^&03C&^

Medium



^&03D&^

LOW

11. Sound Type



^&03E&^

MCU Sound ON(*)



^&03F&^

Scan Head Sound ON

12. Sound frequency setting



^&04C&^

Sound frequency 2048HZ



^&04D&^

Sound frequency 2700HZ

13. Sleep Time Set



^&040&^

No Sleep



^&041&^
Sleep now



^&042&^
10S



^&043&^
30S



^&044&^
1min(*)



^&045&^
2 min



^&046&^
5min



^&047&^
10min



^&048&^
30min

14. GS (group separator) characters conversion



^&060&^
None(*)



^&061&^
GS converts to <GS>



GS converts to |



GS converts to]



GS converts to ^]

15. Letter case conversion



Normal Letter Case(*)



All Uppercase



All Lowercase



Case Inversion

16. Language Set



^&080&^

USA(*)



^&081&^

German



^&082&^

France



^&083&^

Italy



^&084&^

Canadian



^&085&^

Spain



^&086&^

Brazil



^&087&^

Sweden



^&088&^

Portugal



^&089&^

Belgium



^&08A&^

Turkey F



^&08B&^

Turkey Q



^&08C&^

Italian14



^&08D&^

Netherlands



^&08E&^

Poland



^&08F&^

Finland



^&090&^

Latin America



^&091&^

Serbia



^&092&^

Hungary



^&093&^

Denmark



^&094&^

Norway



^&095&^


Japanese

17. ① 2.4G Wireless Setting Private



Receiver Mode(*)

② 2.4G Pairing



Receiver Pairing

1. There are two ways to enter 2.4G pairing:

- (1) Scan the pairing receiver setting code to enter the 2.4G pairing mode;
- (2) Press and hold the button for 8 seconds to hear the first sound, continue to press and hold until the sound is heard again (about 16 seconds in total) and then release the button, it will automatically enter 2.4 wireless and enter the pairing mode

2. Exit 2.4G pairing:

- (1) When the Bluetooth is paired, it will prompt once and end the pairing.
- (2) Double-click the button twice to exit, and it will prompt once.
- (3) When waiting for 1 minute, it will automatically exit and prompt three times.

Note: When exiting pairing, if no new receiver is connected, the receiver that was paired for the last time will be automatically connected by default.



Receiver Mode(*)



Receiver Pairing

Enable

Long press 16S to enter 2.4G pairing

Disable

Long press 16S to turn off 2.4G pairing

③ 2.4G Extended Cache Setting



Disable 2.4G Extended Cache(*)

Remark

1. Close: After scanning the data, it will be uploaded. You need to wait for the data to be uploaded before scanning the next one.
2. On: The scanned data is saved in the cache, and then the next one can be scanned without waiting for the transfer to complete. Automatically store the cache, and then send the data.



Enable 2.4G Extended Cache

21. Bluetooth Setting Private

① Bluetooth HID Setting Private



Bluetooth HID Mode

Note: Set the Bluetooth HID mode, it will enter the Bluetooth HID mode, and automatically connect to the last paired Bluetooth by default. Not in the broadcast state, if you need to pair, check the Bluetooth HID pairing details.



Bluetooth HID Pairing

1. Enter the Bluetooth HID pairing mode:

(1) Set up Bluetooth pairing, and you can search for Bluetooth through Bluetooth devices.

(2) Press and hold the button for 8 seconds, hear the first sound, release it, it will enter the Bluetooth HID mode and set the Bluetooth pairing. It can be searched and paired by Bluetooth devices.

2. Exit Bluetooth HID pairing:

(1) When the Bluetooth is paired, it will prompt once and end the pairing.

(2) Double-click the button twice to exit, and it will prompt once.

(3) Wait for 1 minute, if the Bluetooth is not paired, it will automatically exit and prompt three times.

Note: When exiting pairing, if no new device is connected, the old device that was paired for the last time will be automatically connected by default.



^&C25&^

Enable

Long press 8S to enter Bluetooth HID pairing



^&C26&^

Disable

long press 8S to turn off Bluetooth HID pairing

18. Show or Hide the Keyboard in IOS



Show or hide virtual keyboard under IOS system

Note: In HID mode, IOS system, quickly press 3 times to display or hide the IOS virtual keyboard

19. Bluetooth HID Transfer Rate

1. It is recommended to use fast upload under IOS
2. Under Android, you can set the corresponding speed according to the response speed of the mobile phone

When uploading content is garbled or data is lost, please lower the speed



20. Bluetooth SPP Mode



^&013&^

Bluetooth SPP Mode

21. Bluetooth BLE Mode



^&012&^

Bluetooth BLE Mode

22. Bluetooth Name Setting



^&C0C&^XXX

Bluetooth name barcode customized

- 1.Fixed front character“^&C0C&^”,‘XXX’ is the name of the setting.
- 2.Setting the maximum length of the name:24 bytes.



^&COD&^

Bluetooth name ASCII customized

step:

1. Scan the setting code "Bluetooth name ASCII customized"
2. Scan the content you need to add in turn, please find the ASCII code table
3. Finally scan the setting code "Save data and exit"

Note: The Bluetooth name can be set to a maximum of 24 bytes.

Setting tutorial: You can refer to the tutorial on adding prefixes and suffixes



^&COE&^

Bluetooth Name Default

Remarks: Set the bluetooth name to restore the factory, and the set bluetooth name will be automatically cleared. Or sweeping the factory reset will also clear the custom bluetooth name.

23. Get Bluetooth Name



^&C10&^

Get Bluetooth Name

Note: Only in the blue HID/SPP/BLE mode, the acquisition of the bluetooth name can be successful, otherwise it will fail.

24. Get Bluetooth Address



^&C11&^

Get Bluetooth Address

Remarks: Only in HID/SPP/BLE mode, the acquisition of the Bluetooth address can be successful, otherwise it will fail. The Bluetooth address cannot be displayed, and the serial port can be used to view the address for debugging.

25. Software Update



^&BF0&^
Scanner



^&FF0&^
Receiver



^&CF0&^
Bluetooth

26. Data editor

1). Suffix Terminator character Setting

Add character format: Decode Data+Terminator.



^&300&^

Suffix-None



^&301&^

Suffix-Enter(*)



^&302&^

Suffix-Line



^&303&^

Suffix-Tab



^&304&^

Suffix-Enter&Line

2) . Hidden character Settings



^&306&^

Hide previous character



^&307&^

Hide back character

3)Add prefix and suffix Settings



^&308&^

Add Prefix setting



^&309&^

Add Suffix Setting



^&305&^

Save data and exit

hide front character setting

step:

- (1) Scan the setting code "Hide previous characters"
- (2) Set the first digit of the number to start hiding, and use a two-digit data code to represent the decimal number XX
- (3) Set how many digits (including its own data) are hidden from the beginning of the first digit, and use a two-digit data code to represent the decimal number YY
- (4) Finally, scan the setting code "save data and exit".

XX represents the number of digits in the number, that is, it is hidden from the number of characters in the number (including itself);

YY represents how many digits to hide, that is, how many digits to hide in the future

For example: the barcode content is: "ABCDEFGHJKLMN", hide the DEFGH characters, so that the output barcode is "ABCDIJJKLMN".

- (1) Scan the setting code "Hide previous characters"
- (2) The position of the character 'E' is the 4th bit, so "XX" is '0', '4', Find the data code table and scan the data code table '0' and '4' in turn;
- (3) Hidden "DEFGH" means a total of 5 characters, so "YY" is '0', '5', Find the data code table and scan the data code table '0' and '5' in turn;
- (4) Finally, scan the setting code "save data and exit".

Remarks: Only operate (1) and (4), then it can also be cleared by clearing the character settings before hiding or restoring to the factory.

Hidden back character settings

step:

- (1) Scan the setting code "hidden characters"
- (2) Set the penultimate digit to start hiding (including its own data), and use a two-digit data code to represent the decimal number XX
- (3) Set how many digits to hide from the last digit, and use the two-digit data code to represent the decimal number YY
- (4) Finally, scan the setting code "save data and exit".

XX represents the penultimate digit, that is, it is hidden from the penultimate character (including itself);

YY represents how many digits to hide, that is, how many digits to hide ahead
 For example: the barcode content is: "ABCDEFGHijklmn", hide the DEFGH characters, so that the output barcode is "ABCDijklmn".

- (1) Scan the setting code "Hide previous characters"
- (2) The position of the character 'H' is the 7th bit, so "XX" is '0', '7',
 Find the data code table and scan the data code table '0' and '7' in turn;
- (3) Hidden "DEFGH" means a total of 5 characters, so "YY" is '0', '5',
 Find the data code table and scan the data code table '0' and '5' in turn;
- (4) Finally, scan the setting code "save data and exit".

Remarks: Only operate (1) and (4) to clear the hidden character settings or restore the factory.

Add prefix settings

step:

- (1) Scan the setting code "Add prefix"
- (2) Set the first digit to start inserting characters (including its own data), and use the two-digit "data code" to represent the decimal number XX (the first setting can be omitted and set to "0", "1"), please check the corresponding data code table
- (3) Scan the content to be added in turn, please find the ASCII code table
- (4) Finally, scan the setting code "save data and exit".

For example: the original barcode content is "ABCDEFGHijklmn";

The content after adding the prefix is ""ABCDE12345FGHijklmn"".

1. Scan the setting code "Add Prefix"
2. In the original barcode, the prefix content "12345" is added in front of the character 'F', while the original barcode the position of the code content 'F' is the 6th character, so the data code "XX" is "0", "6", look up the data code table, and scan the barcode corresponding to the data code in turn.
3. The content added to the original barcode is "12345", a total of 5 characters. Find the ASCII code table, the characters "1", "2", "3", "4", "5" correspond to the ASCII codes "31", "32", "33", "34", "35" in turn, and scan the corresponding barcode in turn
4. Finally scan the setting code "Save data and exit".

Remarks: Only operate (1) and (4), then adding a prefix for clearing or restoring to the factory can also be cleared.

Add suffix settings
step

(5) Scan the setting code "Add Suffix"

(6) Set the penultimate digit to start inserting characters (including its own data), and use the two-digit "data code" to represent the decimal number XX (the last setting can be omitted and set to "0", "1"), please check the corresponding Data code table

(7) For the content that needs to be added in one scan, please find the ASCII code table

(8) Finally, scan the setting code "save data and exit".

For example: the original barcode content is "ABCDEFGHJKLMN";

The content after adding the prefix is ""ABCDE12345FGHIJKLMN"".

1. Scan the setting code "Add Suffix"

2. In the original barcode, the suffix content "12345" is added after the character 'E', while the original barcode the position of the code content "E" is the 10th character from the bottom, so the data code "XX" is "1", "0", look up the data code table, and scan the barcode corresponding to the data code in turn.

3. The content added to the original barcode is "12345", a total of 5 characters. Find the ASCII code table, the characters "1", "2", "3", "4", "5" correspond to the ASCII codes "31", "32", "33", "34", "35" in turn, and scan the corresponding barcode in turn

4. Finally scan the setting code "Save data and exit".

Remarks: Only operate (1) and (4), it can also be cleared by adding suffix content for clearing or restoring to the factory.

27. Hide front character shortcut settings

Note: How many digits are hidden from the first digit by default

The format is as follows: ^&600&^ to ^&6FF&^, 00~FF are hidden digits



hide the first 1 bit



2bit



3bit



^&605&^

5bit

4bit



^&606&^

6bit



^&607&^

7bit



^&608&^

8bit



^&609&^

9bit



^&60A&^

10bit



^&60B&^

11bit



^&60C&^

12bit



^&60D&^

13bit



^&60E&^

14bit



^&60F&^

15bit

28. Hide the following characters shortcut settings

Note: By default, how many digits are hidden from the last one

The format is as follows: ^&700&^ to ^&7FF&^, 00~FF are hidden digits



^&701&^

1bit



^&702&^

2bit



^&703&^

3bit



^&704&^

4bit



^&705&^

5bit



^&706&^

6bit



^&707&^

7bit



^&708&^

8bit



^&709&^

9bit



^&70A&^

10bit



^&70B&^

11bit



^&70C&^

12bit



^&70D&

13bit



^&70E&





14bit







^&70F&































15bit

Data Code Table































	 ^&3F0& 0	
 ^&3F1& 1		 ^&3F2& 2
	 ^&3F3& 3	































 $\text{\^{\&}3F4\&}$ 4		 $\text{\^{\&}3F5\&}$ 5
	 $\text{\^{\&}3F6\&}$ 6	
 $\text{\^{\&}3F7\&}$ 7		 $\text{\^{\&}3F8\&}$ 8
	 $\text{\^{\&}3F9\&}$ 9	































ASCII Code Table		
	 $\text{\^{\&}400\&}$ Null	
 $\text{\^{\&}401\&}$ SOH(start of headline)	 $\text{\^{\&}402\&}$ STX (start of text)	 $\text{\^{\&}403\&}$ ETX

 ^&404&^ EOT	 ^&405&^ ENQ	 ^&406&^ ACK
 ^&407&^ BEL	 ^&408&^ BS	 ^&409&^ HT
 ^&40A&^ LF	 ^&40B&^ VT	 ^&40C&^ FF
 ^&40D&^ CR	 ^&40E&^ SO	 ^&40F&^ SI
 ^&410&^ DLE	 ^&411&^ DC1	 ^&412&^ DC2
 ^&413&^ DC3	 ^&414&^ DC4	 ^&415&^ NAK
 ^&416&^ SYN	 ^&417&^ ETB	 ^&418&^ CAN
 ^&419&^ EM	 ^&41A&^ SUB	 ^&41B&^ ESC
 ^&41C&^ FS	 ^&41D&^ GS	 ^&41E&^ RS
 ^&41F&^ US	 ^&420&^ SP	 ^&421&^ !



 ^&422&^ "	 ^&423&^ #	 ^&424&^ \$
 ^&425&^ %	 ^&426&^ &	 ^&427&^ ,
 ^&428&^ (^&429&^)	 ^&42A&^ *
 ^&42B&^ +	 ^&42C&^ ,	 ^&42D&^ -
 ^&42E&^ .	 ^&42F&^ /	 ^&430&^ 0
 ^&431&^ 1	 ^&432&^ 2	 ^&433&^ 3
 ^&434&^ 4	 ^&435&^ 5	 ^&436&^ 6
 ^&437&^ 7	 ^&438&^ 8	 ^&439&^ 9
 ^&43A&^ :	 ^&43B&^ ;	 ^&43C&^ <
 ^&43D&^ =	 ^&43E&^ >	 ^&43F&^ ?

 ^&440&^ @	 ^&441&^ A	 ^&442&^ B
 ^&443&^ C	 ^&444&^ D	 ^&445&^ E
 ^&446&^ F	 ^&447&^ G	 ^&448&^ H
 ^&449&^ I	 ^&44A&^ J	 ^&44B&^ K
 ^&44C&^ L	 ^&44D&^ M	 ^&44E&^ N
 ^&44F&^ O	 ^&450&^ P	 ^&451&^ Q
 ^&452&^ R	 ^&453&^ S	 ^&454&^ T
 ^&455&^ U	 ^&456&^ V	 ^&457&^ W
 ^&458&^ X	 ^&459&^ Y	 ^&45A&^ Z
 ^&45B&^ [ ^&45C&^ \	 ^&45D&^]

 ^&45E&^ ^ ^	 ^&45F&^ - ^	 ^&460&^ , ^
 ^&461&^ a ^	 ^&462&^ b ^	 ^&463&^ c ^
 ^&464&^ d ^	 ^&465&^ e ^	 ^&466&^ f ^
 ^&467&^ g ^	 ^&468&^ h ^	 ^&469&^ i ^
 ^&46A&^ j ^	 ^&46B&^ k ^	 ^&46C&^ l ^
 ^&46D&^ m ^	 ^&46E&^ n ^	 ^&46F&^ o ^
 ^&470&^ p ^	 ^&471&^ q ^	 ^&472&^ r ^
 ^&473&^ s ^	 ^&474&^ t ^	 ^&475&^ u ^
 ^&476&^ v ^	 ^&477&^ w ^	 ^&478&^ x ^
 ^&479&^ y ^	 ^&47A&^ z ^	 ^&47B&^ { ^

 ^&47C&^ 	 ^&47D&^ }	 ^&47E&^ ~
 ^&47F&^ DEL	 ^&480&^ Caps Lock	 ^&481&^ F1
 ^&482&^ F2	 ^&483&^ F3	 ^&484&^ F4
 ^&485&^ F5	 ^&486&^ F6	 ^&487&^ F7
 ^&488&^ F8	 ^&489&^ F9	 ^&48A&^ F10
 ^&48B&^ F11	 ^&48C&^ F12	 ^&48D&^ PrintScreen
 ^&48E&^ Scroll Lock	 ^&48F&^ Pause	 ^&490&^ Insert
 ^&491&^ Home	 ^&492&^ PageUp	 ^&493&^ Delete
 ^&494&^ PageDown	 ^&495&^ End	 ^&496&^ RightArrow
 ^&497&^ LeftArrow	 ^&498&^ DownArrow	 ^&499&^ UpArrow

 ^&49A&^ Num Lock(keypad)	 ^&49B&^ /(keypad)	 ^&49C&^ *(keypad)
 ^&49D&^ -(keypad)	 ^&49E&^ +(keypad)	 ^&49F&^ Enter(keypad)
 ^&4A0&^ 1(keypad)	 ^&4A1&^ 2(keypad)	 ^&4A2&^ 3(keypad)
 ^&4A3&^ 4(keypad)	 ^&4A4&^ 5(keypad)	 ^&4A5&^ 6(keypad)
 ^&4A6&^ 7(keypad)	 ^&4A7&^ 8(keypad)	 ^&4A8&^ 9(keypad)
 ^&4A9&^ 0(keypad)	 ^&4AA&^ .(keypad)	AB~CF 保留 待用
Add Ctrl、Shift、Alt、GUI function		
Need to pay attention: there must be a press, there must be a release, the press and release must be used in pairs Otherwise, there will be hotkey problems such as data not uploading and the computer's inexplicable lock screen.		
 ^&4D0&^ L-Ctrl Press	 ^&4D1&^ L-Shift Press	 ^&4D2&^ L-Alt Press
 ^&4D3&^ L-GUI Press	 ^&4D4&^ R-Ctrl Press	 ^&4D5&^ R-Shift Press
 ^&4D6&^ R-Alt Press	 ^&4D7&^ R-GUI Press	

 \^&4D8\^ L-Ctrl Release	 \^&4D9\^ L-Shift Release	 \^&4DA\^ L-Alt Release
 \^&4DB\^ L-GUI Release	 \^&4DC\^ R-Ctrl Release	 \^&4DD\^ R-Shift Release
 \^&4DE\^ R-Alt Release	 \^&4DF\^ R-GUI Release	E0~FF Reserve